



2003 Perimeter Rd
Suite E
Greenville, SC 29605-5276
Phone (864) 277-1560
Fax (864) 277-1561
www.PhillipTech.com

Product Specifications

TAN05RCSS

Silver, 5 MHz RC Quartz Crystals



Description: Quartz sensor with enhanced high temperature resistance for use in Ulvac and Sloan instruments.

Physical Specification:

- 1) **Material:** Pure Silicon Dioxide monocrystal, Electronic Grade Quartz with Bechmann optimized Geometry and enhanced energy trapping of the fundamental mode.
- 2) **Dimensions:** 0.550" \pm .000/- .002" OD
- 3) **Contour:** plano convex
- 4) **Finish:** 7 microns rms roughness plano and contour sides
- 5) **Defects:** No chips, scratches or etch marks within a 13.95 mm diameter clear aperture
- 6) **Electrodes:** "Ulvac" patterned silver with Oxygen reactive intermediate layer for improved thin-film integrity.

Electrical Specification:

- 1) **Resonant Frequency:** 4.990-4.999 MHz, fundamental series resonance
- 2) **Resistance:** <40 Ohms, plated
- 3) **Contact Resistance:** <10 Ohms edge to edge on pattern side
- 4) **Spurious Modes:** First Anharmonic >150 KHz above fundamental

Appearance:

- 1) No misaligned electrodes
- 2) No uneven coloration
- 3) No off-center patterns
- 4) No scratches, scuffs, or etch markings present
- 5) No chips or cracks